



250 CFM PORTABLE AFTERCoolERS

ACSE250-12V-CH

CHICAGO INLET & CHICAGO OUTLET

ACSE250-12V-4P

4-PRONG INLET & 4-PRONG OUTLET



STANDARD SPECIFICATIONS:

- CHICAGO AND 4-PRONG SET-UPS STANDARD
- 40 MICRON AIR FILTER/SEPARATOR WITH A 1QT. RESERVOIR AND MANUAL DRAIN
- 50FT. 16.2 POWER CORD WITH CLAMPS
- 1-1/4" PIPING FORMAT
- STEEL CONSTRUCTED STAND, FIN GUARD, HANDLE AND PROTECTIVE CORD WRAP
- RATED 250 CFM OF AIRFLOW
- MAXIMUM PSI: 150PSI
- SHIPPING/ASSEMBLED WEIGHT: APPROXIMATELY 68 POUNDS
- APPROXIMATE DIMENSIONS ASSEMBLED: 36"w x 23"h x 14"d

OPTIONS:

- CUSTOM INLET AND OUTLET SETUPS WITH BALL VALVES
- TWIST LOCK EXTENSION CORDS IN 50' AND 100' INCREMENTS
- 120V AC TO 12V DC CONVERTERS



375 CFM PORTABLE AFTERCoolERS

ACSE375-12V-4P

4-PRONG INLET & 4-PRONG OUTLET



STANDARD SPECIFICATIONS:

- 4-PRONG SET-UPS STANDARD
- 40 MICRON AIR FILTER/SEPARATOR WITH A 1QT. RESERVOIR AND MANUAL DRAIN
- 50FT. 16.2 POWER CORD WITH CLAMPS
- 1-1/4" PIPING FORMAT
- STEEL CONSTRUCTED STAND, FIN GUARD, HANDLE AND PROTECTIVE CORD WRAP
- RATED 375 CFM OF AIRFLOW
- MAXIMUM PSI: 150PSI
- SHIPPING/ASSEMBLED WEIGHT: APPROXIMATELY 82 POUNDS
- APPROXIMATE DIMENSIONS ASSEMBLED: 40"w x 27"h x 14"d

OPTIONS:

- CUSTOM INLET AND OUTLET SETUPS WITH BALL VALVES
- TWIST LOCK EXTENSION CORDS IN 50' AND 100' INCREMENTS
- 120V AC TO 12V DC CONVERTERS