

# Compressed Air



## T155AK 300 PSI Textile Cord "Air Drill" Hose



TWRS PART NUMBER	GOLD BRAID AIR HOSE DESCRIPTION
AHGB125300	AIR HOSE 1-1/4" I.D. 300 PSI
AHGB150300	AIR HOSE 1-1/2" I.D. 300 PSI
AHGB200300	AIR HOSE 2" I.D. 300 PSI
AHGB300300	AIR HOSE 3" I.D. 300 PSI

**Applications:**

High quality air hose for mining and construction service.

**Cover:**

Yellow SBR – abrasion and ozone-resistant.

**Reinforcement:**

Spiraled, high tensile textile cords.

**Tube:**

Black SBR/NBR blend – oil mist resistant.

**Working Pressure:**

Constant Pressure – 20 Bar (300 PSI)

**Temperature Range:**

-22°F (-30°C) to 176°F (+80°C)

**Branding:**

ALFAGOMMA – ITALY – T155 20 BAR (300 PSI) AIR (in blue letters)

**Standard Length:**

100 feet: 1/2" through 4"

50 feet: 1/2", 1" and 2" through 4"

### Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T155AK050	1/2	13	0.83	21	300	0.22
T155AK075	3/4	19	1.14	29	300	0.38
T155AK100	1	25	1.38	35	300	0.48
<b>T155AK125</b>	<b>1 1/4</b>	<b>32</b>	<b>1.73</b>	<b>44</b>	<b>300</b>	<b>0.60</b>
<b>T155AK150</b>	<b>1 1/2</b>	<b>38</b>	<b>1.97</b>	<b>50</b>	<b>300</b>	<b>0.70</b>
<b>T155AK200</b>	<b>2</b>	<b>51</b>	<b>2.56</b>	<b>65</b>	<b>300</b>	<b>1.12</b>
T155AK250	2 1/2	63	3.11	79	300	1.55
<b>T155AK300</b>	<b>3</b>	<b>76</b>	<b>3.62</b>	<b>92</b>	<b>300</b>	<b>1.89</b>
T155AK400	4	102	4.65	118	300	2.47

**COUPLING SUGGESTIONS**

Steel or malleable iron male insert NPT, female ground joint or washer type with spud, attached with 2 or 4 bolt interlocking clamps or bands.

Universal couplings may be used on sizes (1/2" – 2")

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.